



Universität Karlsruhe (TH)
Forschungsuniversität • gegründet 1825

Versuchsanstalt für
Stahl, Holz und Steine
Amtliche Materialprüfungsanstalt



EG-CERTIFICATE OF CONFORMITY

0769-CPD-6019

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member State relating to the construction products (Construction Products Directive CPD), amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

Glued Laminated Timber
Product specifications see page 2

placed on the marked by

Gebr. Schütt KG GmbH & Co.
Am Bahnhof 20
25572 Landscheide

and produced in the factory

Am Bahnhof 20
25572 Landscheide

is submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the notified body -Versuchsanstalt, für Stahl, Holz und Steine- has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in the Annex ZA of the standard

EN 14080:2005

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on 11 May 2009 and remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Karlsruhe, 11 May 2009

Head of Certification Body



H. J. Blaß
Univ.-Prof. Dr.-Ing. H. J. Blaß

Construction Product:

Glued Laminated Timber

Strength Classes:	GL24, GL28 and GL32
Characteristic Values:	according to EN 1194
Service Classes:	SC 1, SC 2 und SC 3
Wood Species:	Spruce / Fir
Type of Adhesive:	Melamine-Urea Formaldehyde adhesive (MUF)
Reaction to Fire:	D-s2, d0
Formaldehyde Emission:	E1
Natural Durability:	4